


# Neo-Duct® Neoprene Ducting Hose Series HTNP2 - Black

*Neoprene-coated two-ply polyester ducting for dust collection, air movement, fume control and light material handling.*



## FEATURES & BENEFITS

- **Double-ply construction** — works extremely well in both positive and negative pressure applications . . . offers extreme flexibility and compressibility, combined with excellent crush-resistance and tensile strength. Recommended for all air handling applications, dust and fume control and light material handling.
- **Neoprene coating with polyester fabric construction** — provides excellent flexibility . . . will not rot.
- **Manufactured to meet UL94V-O rating.**
- **Standard packaging: 25' lengths in cartons.**

**Service Temperature Range: -65°F (-54°C) to +250°F (+127°C)**

## Neo-Duct Double Ply, Wire-Reinforced Flexible Fabric Ducting Hoses

Series No.	Nominal Size ID		Min. Bending Radius		Max. W.P. (PSI)	Hose Weight (lbs/ft)
	(In)	(mm)	(In)	(mm)		
HTNP2-150X25	1 1/2	38.1	2.6	66.0	32	.16
HTNP2-200X25	2	50.8	3.5	88.9	30	.22
HTNP2-250X25	2 1/2	63.5	4.0	101.6	28	.28
HTNP2-300X25	3	76.2	5.0	127.0	25	.33
HTNP2-350X25	3 1/2	88.9	5.7	144.8	24	.42
HTNP2-400X25	4	101.6	6.5	165.1	23	.48
HTNP2-500X25	5	127.0	7.5	190.5	22	.61
HTNP2-600X25	6	152.4	9.0	228.6	21	.70
HTNP2-700X25	7	177.8	9.5	241.3	20	.92
HTNP2-800X25	8	203.2	10.0	254.0	19	1.04
HTNP2-1000X25	10	254.0	11.0	279.4	18	1.36
HTNP2-1200X25	12	304.8	13.5	342.9	17	1.85
HTNP2-1400X25	14	355.6	15.5	393.7	16	2.10
HTNP2-1600X25	16	406.4	18.5	469.9	15	2.40
HTNP2-1800X25	18	457.2	22.0	558.8	6	2.70
HTNP2-2000X25	20	508.0	24.0	609.6	4	3.00

Please call your local Kuriyama Warehouse location for availability of products/sizes shown. Plain ends are supplied with standard ducting lengths. An additional charge of 10% is added for non-standard lengths. Cuffs (Approximately 6" in length) are available upon request.

The trademarks contained in this publication are trademarks of Kuriyama of America, Inc.



# Kuriyama of America, Inc.

Visit us  
[www.kuriyama.com](http://www.kuriyama.com)  
on the Web!

PLEASE REFER TO CURRENT KURIYAMA TERMS, CONDITIONS AND LIMITED WARRANTY OF SALE ISSUED 9/2005

All prices and specifications subject to change without notice.

KNDPL0810

# Cautionary Statement

All Products sold and distributed by Kuriyama of America, Inc. are in the nature of commodities and they are sold by published specifications and not for particular purposes, uses or applications. Purchaser shall first determine their suitability for the intended purposes, uses or applications and shall either conduct its own engineering studies or tests, or retain qualified engineers, consultants or testing laboratories and consult with them before determining the proper use, suitability or propriety of the merchandise or Products for the intended purposes, uses or applications.

Kuriyama of America, Inc. ("Seller") does not recommend the Products for any particular purpose, use or application, and the Purchaser or user thereof shall assume full responsibility for the suitability, propriety, use and application of the Products. Purchaser shall follow all instructions contained in Seller's catalogs, brochures, technical bulletins and other documents regarding the Products. The Products, including but not limited to, hose, tubing or couplings, may fail due to the use or conveyance of substances at elevated or lowered temperatures or at excessive pressure, the conveyance of abrasive, injurious, flammable, explosive or damaging substances.

Hose or tubing used in bent configurations will be subjected to increased abrasion. Hose clamps or couplings may loosen after initial installation and all sections of hose and tubing including connections, couplings, clamps, conductivity and bonding should be inspected frequently, regularly and consistently, and should be replaced, adjusted or re-tightened for the avoidance of leakage, for the prevention of injuries or damages, and for general safety purposes. Except as indicated in its Limited Warranty, Seller shall not be liable or responsible for direct or indirect injuries or damages caused by or attributed to the failure or malfunction of any Products sold or distributed by it.

Purchasers or users of the Products should frequently and consistently undertake inspections and protective measures with respect to the use and application of Products, which should include the examination of tube and cover, conditions of the hose or tubing, and the identification, repair or replacement of sections showing cracking, blistering, separations, internal and external abrasions, leaking or slipped couplings or connections and make proper proof tests.

## Limited Warranty

The Products sold or distributed by Seller are warranted to its customers to be free from defects in material and workmanship at the time of shipment by us, subject to the following provisions. ALL WARRANTY CLAIMS SHALL BE MADE WITHIN SIX (6) MONTHS AFTER SELLER SHIPPED THE PRODUCTS. SELLER'S LIABILITY HEREUNDER IS LIMITED AT SELLER'S EXCLUSIVE DISCRETION, TO 1) THE PURCHASE PRICE OF ANY PRODUCTS PROVING DEFECTIVE; 2) REPAIR OF ANY DEFECTIVE PRODUCT OR PART THEREOF; OR 3) REPLACEMENT OF ANY DEFECTIVE PRODUCT OR PART UPON ITS AUTHORIZED RETURN TO SELLER.

THIS WARRANTY IS IN LIEU OF AND EXCLUDES ALL OTHER WARRANTIES, EXPRESSED, IMPLIED, STATUTORY, OR OTHERWISE CREATED UNDER APPLICABLE LAW INCLUDING, BUT NOT LIMITED TO, THE WARRANTY OF MERCHANTABILITY AND THE WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT SHALL SELLER OR THE MANUFACTURER OF THE PRODUCT BE LIABLE FOR SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING LOSS OF PROFITS, WHETHER OR NOT CAUSED BY OR RESULTING FROM THE NEGLIGENCE OF SELLER AND/OR THE MANUFACTURER OF THE PRODUCT, UNLESS SPECIFICALLY PROVIDED HEREIN. IN ADDITION, THIS WARRANTY SHALL NOT APPLY TO ANY PRODUCTS OR PORTIONS THEREOF WHICH HAVE BEEN SUBJECTED TO ABUSE, MISUSE, IMPROPER INSTALLATION, MAINTENANCE, OR OPERATION, ELECTRICAL FAILURE OR ABNORMAL CONDITIONS, AND TO PRODUCTS WHICH HAVE BEEN TAMPERED WITH, ALTERED, MODIFIED, REPAIRED, REWORKED BY ANYONE NOT APPROVED BY SELLER, OR USED IN ANY MANNER INCONSISTENT WITH THE PROVISIONS OF THE "CAUTIONARY STATEMENT" ABOVE OR ANY INSTRUCTIONS OR SPECIFICATIONS PROVIDED WITH OR FOR THE PRODUCT.

09/2005

Distributed by:



## Kuriyama of America, Inc.

Headquarters, Sales Office and Stocking Location

360 E. State Parkway, Schaumburg, IL 60173-5335

Phone: (847) 755-0360 • Toll-free FAX: (800) 800-0320

International FAX: (847) 885-0996

Web Site: <http://www.kuriyama.com>

E-Mail: [sales@kuriyama.com](mailto:sales@kuriyama.com)

## SALES OFFICES — CONTACT THE LOCATION BELOW WHICH SERVES YOUR AREA

### SOUTHWEST WAREHOUSE KURIYAMA OF AMERICA, INC. HOUSTON

8919 MARKET ST.  
HOUSTON, TX 77029  
Phone: (713) 674-8212  
Toll Free Phone: (800) 501-6808  
FAX: (713) 674-5214  
Toll Free FAX: (800) 800-5214

### WESTERN WAREHOUSE KURIYAMA OF AMERICA, INC. SANTA FE SPRINGS

10749 SHOEMAKER AVENUE  
SANTA FE SPRINGS, CA 90670-4039  
Phone: (562) 941-4507  
FAX: (562) 941-8940  
Toll-Free FAX: (800) 326-8940

### SOUTHEAST WAREHOUSE FORTNEY SALES CO., INC.

1580 BIG SHANTY DR NW  
KENNESAW, GA 30144-7040  
Phone: (770) 427-6528  
FAX: (770) 423-9249  
Toll Free FAX: (800) 423-9249  
Web Site: [www.fortneysales.com](http://www.fortneysales.com)  
E-Mail: [sales@fortneysales.com](mailto:sales@fortneysales.com)

### EASTERN WAREHOUSE EASTERN RUBBER & PLASTICS CO., INC.

RT. 537 - PLUMSTED INDUSTRIAL PARK  
NEW EGYPT, NJ 08533-0248  
Phone: (609) 758-0100  
FAX: (609) 758-0102  
Toll Free FAX: (800) 445-7138  
Web Site: [www.easternrubber.com](http://www.easternrubber.com)  
E-Mail: [sales@easternrubber.com](mailto:sales@easternrubber.com)

### IN MEXICO:

KURIYAMA DE MEXICO, S. DE R.L. DE C.V.  
CARRETERA MIGUEL ALEMÁN KM. 14.8  
PARQUE INDUSTRIAL HASNA  
APODACA (MONTERREY), N.L., 66600, MEXICO  
Phone: (81) 1086-1870 O 71  
Toll-Free: (within Mexico) 01-800-822-52-00  
FAX: (81) 1086-1869  
Internet: [www.kuriyama.com](http://www.kuriyama.com)  
Correo Electronico: [ventas@kuriyama.com](mailto:ventas@kuriyama.com)



Visit us  
[www.kuriyama.com](http://www.kuriyama.com)  
on the Web!

Printed in U. S. A.

KNDPL0810