


SIL-Duct® Series SDH Silicone Ducting Hose

Two-ply smooth silicone-coated polyester fabric hose with helically-wound spring steel wire for flexibility. Double continuous-filament, silicone-coated fiberglass cord for durability.



FEATURES

- Designed for both high and low temperature extremes.
- Suited for air handling applications at low positive and low negative pressures.
- Resistant to many oils and solvents, ozone, water, fungus, and alkalis.
- Highly effective in both positive and negative pressures.
- Superior air flow and minimum friction loss.
- Lightweight, non-kinking and easy to install.
- Standard Packaging: 12' lengths in cartons.

APPLICATIONS

- Plastic processing dryers.
- Air handling applications.
- Dust and fume control.
- Light material handling.

Service Temperature Range: -80°F (-62°C) to +600°F (+316°C)

SIL-Duct® Series SDH Silicone Ducting Hose

Part Number	ID (In)	Wall Thickness	P.S.I.G.	Burst	Max Neg. PSI	Max Leakage CFM	Cuff Length	WT. per ft in oz.	Length/ CTN.
SDH-100X12	1"	.070	60	180	15	.015	1-1/2"	2.0	12'
SDH-125X12	1 1/4"	.070	60	180	15	.015	1-1/2"	2.5	12'
SDH-150X12	1 1/2"	.070	55	165	13	.015	1-1/2"	3.0	12'
SDH-175X12	1 3/4"	.070	55	165	13	.020	1-1/2"	3.5	12'
SDH-200X12	2"	.070	50	150	10	.020	1-1/2"	4.0	12'
SDH-250X12	2 1/2"	.070	45	135	8	.025	1-1/2"	5.0	12'
SDH-300X12	3"	.070	45	135	7	.030	1-1/2"	6.2	12'
SDH-400X12	4"	.080	40	120	5	.040	1-1/2"	8.4	12'
SDH-500X12	5"	.080	35	105	4	.060	2"	10.7	12'
SDH-600X12	6"	.090	30	90	3	.100	2"	13.0	12'
SDH-800X12	8"	.110	15	45	3	.150	2"	17.8	12'

Note: Not recommended for liquids or abrasive materials.

The trademarks contained in this publication are trademarks of Kuriyama of America, Inc.



Kuriyama of America, Inc.

Visit us
www.kuriyama.com
on the Web!

PLEASE REFER TO CURRENT KURIYAMA TERMS, CONDITIONS AND LIMITED WARRANTY OF SALE ISSUED 9/2005

All prices and specifications subject to change without notice.

Cautionary Statement

All Products sold and distributed by Kuriyama of America, Inc. are in the nature of commodities and they are sold by published specifications and not for particular purposes, uses or applications. Purchaser shall first determine their suitability for the intended purposes, uses or applications and shall either conduct its own engineering studies or tests, or retain qualified engineers, consultants or testing laboratories and consult with them before determining the proper use, suitability or propriety of the merchandise or Products for the intended purposes, uses or applications.

Kuriyama of America, Inc. ("Seller") does not recommend the Products for any particular purpose, use or application, and the Purchaser or user thereof shall assume full responsibility for the suitability, propriety, use and application of the Products. Purchaser shall follow all instructions contained in Seller's catalogs, brochures, technical bulletins and other documents regarding the Products. The Products, including but not limited to, hose, tubing or couplings, may fail due to the use or conveyance of substances at elevated or lowered temperatures or at excessive pressure, the conveyance of abrasive, injurious, flammable, explosive or damaging substances.

Hose or tubing used in bent configurations will be subjected to increased abrasion. Hose clamps or couplings may loosen after initial installation and all sections of hose and tubing including connections, couplings, clamps, conductivity and bonding should be inspected frequently, regularly and consistently, and should be replaced, adjusted or re-tightened for the avoidance of leakage, for the prevention of injuries or damages, and for general safety purposes. Except as indicated in its Limited Warranty, Seller shall not be liable or responsible for direct or indirect injuries or damages caused by or attributed to the failure or malfunction of any Products sold or distributed by it.

Purchasers or users of the Products should frequently and consistently undertake inspections and protective measures with respect to the use and application of Products, which should include the examination of tube and cover, conditions of the hose or tubing, and the identification, repair or replacement of sections showing cracking, blistering, separations, internal and external abrasions, leaking or slipped couplings or connections and make proper proof tests.

Limited Warranty

The Products sold or distributed by Seller are warranted to its customers to be free from defects in material and workmanship at the time of shipment by us, subject to the following provisions. ALL WARRANTY CLAIMS SHALL BE MADE WITHIN SIX (6) MONTHS AFTER SELLER SHIPPED THE PRODUCTS. SELLER'S LIABILITY HEREUNDER IS LIMITED AT SELLER'S EXCLUSIVE DISCRETION, TO 1) THE PURCHASE PRICE OF ANY PRODUCTS PROVING DEFECTIVE; 2) REPAIR OF ANY DEFECTIVE PRODUCT OR PART THEREOF; OR 3) REPLACEMENT OF ANY DEFECTIVE PRODUCT OR PART UPON ITS AUTHORIZED RETURN TO SELLER.

THIS WARRANTY IS IN LIEU OF AND EXCLUDES ALL OTHER WARRANTIES, EXPRESSED, IMPLIED, STATUTORY, OR OTHERWISE CREATED UNDER APPLICABLE LAW INCLUDING, BUT NOT LIMITED TO, THE WARRANTY OF MERCHANTABILITY AND THE WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT SHALL SELLER OR THE MANUFACTURER OF THE PRODUCT BE LIABLE FOR SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING LOSS OF PROFITS, WHETHER OR NOT CAUSED BY OR RESULTING FROM THE NEGLIGENCE OF SELLER AND/OR THE MANUFACTURER OF THE PRODUCT, UNLESS SPECIFICALLY PROVIDED HEREIN. IN ADDITION, THIS WARRANTY SHALL NOT APPLY TO ANY PRODUCTS OR PORTIONS THEREOF WHICH HAVE BEEN SUBJECTED TO ABUSE, MISUSE, IMPROPER INSTALLATION, MAINTENANCE, OR OPERATION, ELECTRICAL FAILURE OR ABNORMAL CONDITIONS, AND TO PRODUCTS WHICH HAVE BEEN TAMPHERED WITH, ALTERED, MODIFIED, REPAIRED, REWORKED BY ANYONE NOT APPROVED BY SELLER, OR USED IN ANY MANNER INCONSISTENT WITH THE PROVISIONS OF THE "CAUTIONARY STATEMENT" ABOVE OR ANY INSTRUCTIONS OR SPECIFICATIONS PROVIDED WITH OR FOR THE PRODUCT.

09/2005

Distributed by:

The trademarks contained in this publication are trademarks of Kuriyama of America, Inc.



Kuriyama of America, Inc.

Headquarters, Sales Office and Stocking Location

360 E. State Parkway, Schaumburg, IL 60173-5335
Phone: (847) 755-0360 • Toll-free FAX: (800) 800-0320
International FAX: (847) 885-0996

Web Site: <http://www.kuriyama.com>
E-Mail: sales@kuriyama.com

SALES OFFICES — CONTACT THE LOCATION BELOW WHICH SERVES YOUR AREA

SOUTHWEST WAREHOUSE KURIYAMA OF AMERICA, INC. HOUSTON

8919 MARKET ST.
HOUSTON, TX 77029
Phone: (713) 674-8212
Toll Free Phone: (800) 501-6808
FAX: (713) 674-5214
Toll Free FAX: (800) 800-5214

WESTERN WAREHOUSE KURIYAMA OF AMERICA, INC. SANTA FE SPRINGS

10749 SHOEMAKER AVENUE
SANTA FE SPRINGS, CA 90670-4039
Phone: (562) 941-4507
FAX: (562) 941-8940
Toll-Free FAX: (800) 326-8940

SOUTHEAST WAREHOUSE FORTNEY SALES CO., INC.

1580 BIG SHANTY DR NW
KENNESAW, GA 30144-7040
Phone: (770) 427-6528
FAX: (770) 423-9249
Toll Free FAX: (800) 423-9249
Web Site: www.fortneysales.com
E-Mail: sales@fortneysales.com

EASTERN WAREHOUSE EASTERN RUBBER & PLASTICS CO., INC.

RT. 537 - PLUMSTED INDUSTRIAL PARK
NEW EGYPT, NJ 08533-0248
Phone: (609) 758-0100
FAX: (609) 758-0102
Toll Free FAX: (800) 445-7138
Web Site: www.easternrubber.com
E-Mail: sales@easternrubber.com

IN MEXICO:

KURIYAMA DE MEXICO, S. DE R.L. DE C.V.
CARRETERA MIGUEL ALEMÁN KM. 14.8
PARQUE INDUSTRIAL HASNA
APODACA (MONTERREY), N.L., 66600, MEXICO
Phone: (81) 1086-1870 O 71
Toll-Free: (within Mexico) 01-800-822-52-00
FAX: (81) 1086-1869
Internet: www.kuriyama.com
Correo Electronico: ventas@kuriyama.com



Visit us

www.kuriyama.com

on the Web!